

# Hog Ring Plier Type CL24-HR68

The BeA Hog Ring Plier CL24-HR68 takes flexible hog ring staples type CL 24 x 1,8. For reaching tight areas, the tool is fitted with an extended nose. The rear loading magazine allows easy and quick reloading. This is a versatile tool for many different applications.



### Popular applications:

Matresses, automotive seating, bedding, wire cages, fencing, other wire connections, etc.

Length: 351 mm  
Width: 89 mm  
Height: 220 mm

### Technical data

Type description:	<b>HR CL24-HR68</b> Standard
Article code:	12100447
Magazine type :	Rear loader
Safety:	-
Fastener type:	CL 24
Magazine capacity:	140
Fasteners per strip:	2 x 70
Operating pressure:	4 – 7 bar
Max. operating pressure:	7 bar
Air consumption/operation:	1.0 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 84 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 94 dB
Weight:	1.38 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

**Extras supplied with the stapler:** Operating instructions, spare parts list, service instructions

Subject to technical modifications.

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)


Product leaflet CL24-HR68

# Hog Ring Plier Type HR 64-CL24

Staples type CL 24



Joh. Friedrich Behrens AG  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)



Description	W = Width mm
CL 24 x 1,8 NK Flex	24

**Explanations:**

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut