

Pneumatic Tacker Type SK 335-201

The ultra light weight nailer (0,8 kg) drives brad nails type SK 300 in the length from 10 – 35 mm. The non-mar rubber tip prevents scratches. The slim nose and rear-cut magazine allows to reach tight spots. The lock-out mechanism prevents the tool from operating unless brad nails are loaded in the magazine. The indicator signifies reloading timing through its transparent magazine-side. The nailer is equipped with an adjustment for depth control and an adjustable exhaust deflector.



Popular applications:

Glazing strips, furniture assembly, picture frames.

Length: 254 mm
Width: 53 mm
Height: 213 mm

Technical data

Type description:	SK 335-201
Article code:	12100004
Magazine type :	Side loader
Safety:	Single actuation
Fastener type:	Brads SK 300
Magazine capacity:	100
Fasteners per strip:	2 x 50
Operating pressure:	4 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0,46litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 80.6 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 90.8 dB
Weight:	0.8 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive for Machinery (89/392 EWG)

Pneumatic Tacker Type SK 335-201

Brads type SK 300



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
SK 310 NK *	10
SK 315 NK *	15
SK 320 NK	20
SK 325 NK	25
SK 330 NK	30
SK 335 NK	35

The SK 300 brad nails' heads are coloured brown (standard).
Other colours are also available on request.

* without colour.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut