

## Pneumatic Bradder Type SK 338 – 616

A lightweight and particularly well balanced tool. The BeA Pneumatic Bradder SK 338-616 drives finish nails in the length from 22 to 38 mm. The top loading device guarantees quick and safe loading. The nails can be delivered in a variety of head-colours as well as in stainless steel.

The available accessories make the SK 338-616 even more versatile.



### Popular applications:

Glazing strips, wicker work, furniture, corner trims.

Length:	231 mm
Width:	57 mm
Height:	200 mm

### Technical data

Type description:	SK 338-616 Contact	SK 338-616 E Single
Article code:	12000225	12000227
Magazine type :	Top loader	Top loader
Safety:	Contact actuation	Single actuation
Fastener type:	Finish nails SK 300	Finish nails SK 300
Magazine capacity:	125	125
Fasteners per strip:	1 x 100	1 x 100
Operating pressure:	5 – 8 bar	5 – 8 bar
Max. operating pressure:	8 bar	8 bar
Air consumption/operation:	0.9 litre / 6 bar	0.9 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 84 dB	L pA, 1s, d= 84 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 89 dB	L WA, 1 s,d= 89 dB
Weight:	1.6 kg	1.6 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

### Accessories:

Articel code	Description
14400816	Glazier Stop
14403421	Remote valve
14403527	Mounting flange
14403428	Remote valve with additional manual actuation
14406951	Grip elongation

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive for Machinery (89/392 EWG)


## Pneumatic Bradder Type SK 338-616

### SK 300 finish nails



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



Description	L = Length mm
SK 322 NK	22
SK 325 NK	25
SK 330 NK	30
SK 335 NK	35
SK 338 NK	38
SK 335 NR *	35

The SK 300 finish nail heads are coloured brown ( standard ).  
Other lengths and finishes are also available on request.

\* only without colour

#### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut