

Technical data 554DCC

Model number : 554DCC
Type of tool : COIL NAILER
Dimension : 287×130×300
Weight of tool : 2.7kgs

Compressed air
Maximum permissible operating pressure : 8.3 bar
Recommended operating pressure : 5.8 - 8.3 bar
Air consumption per driving operation : 1.3 litres at 7 bar operating pressure

Noise characteristic values in accordance with
LpA : 98.2 dBA
LwA : 102.1 dBA

Vibration : 2.95 m/s²

Recommended lubrications : White oil # 16

Fastener specifications (mm) : Wire collated: Dia. 2.1-2.3mm,
Nail length: 32-55mm

Accessories : **M6/5** mm inner hexagon spanner
Protective goggles
Oil pot

Applications & suitability : Pallets

Actuating system (√ safety yoke installed) : Adjustable trigger for single sequential and continuous fire.

Trigger device : Finger pressure activation

Filling the magazine.

- 1 Release latch to open the door and magazine.
- 2 Adjust the level of the magazine base so that the nails will feed in line with guides.
- 3 Load nails onto pivot in the magazine and full forward so that the nails are inserted into the feeder mechanism.
- 4 On closing the magazine ensure the latch is closed properly.

Declaration of Conformity

We **ZHEJIANG RONGPENG AIR TOOLS CO., LTD.**
Shuiquetou Village, Pengjie Town,
Luqiao, Taizhou, Zhejiang, China

declare under our sole responsibility that the pneumatic nailer 554DCC

conforms with the directive and 2006/42/EC
EN ISO 12100:2010 "Safety of Machinery"
following the provisions of the Directive
Regarding Machinery 2006/42/ EC.
amendments EN 792-13/A1:2008

Serial number:

Signed: Vivian Hong

Date: 07/09/2019